

## **Roto NT Special Surface**

for special applications



**Roto NT**

# Roto NT Special Surface for special applications

NEW

## Maximum surface protection in the familiar Roto top quality

Roto NT stands for the biggest-selling Tilt&Turn technology that meets the most stringent requirements with regard to quality, reliability and durability. That's not without good reason, because Roto NT is constantly setting high standards through new developments. The Roto NT special surface – sealing the high Roto quality standard yet again. Following the basic galvanic sealing, each individual NT component has a special coating applied to it with extreme care. This is a time-consuming process so that the special surface will be able to withstand the most adverse conditions for a long time.

## Areas of use

The Roto NT special surface provides the greatest resistance wherever unusual ambient conditions prevail, e. g.

- Coastal areas with salty, moist air
- Swimming baths with chlorine/ozone vapours combined with humidity
- Cattle stables with heavy ammoniac gas build-ups
- Accoya wood windows containing aggressive agents such as acetic acid

The result: The high quality of the Roto NT window technology is maintained for a long time.

## The advantages at a glance

- Maximum available corrosion protection on all NT components with a special surface
- Functional capability and durability even under extreme conditions
- Maximum resistance to extreme environmental influences
- Robust against aggressive acids, gases and alkalis
- An even, matt silver appearance

## The new Roto NT special surface with an elegant silver appearance

All NT components are given a special coating after the basic galvanic seal with extreme care. Only in this way is it possible to achieve maximum surface protection





### **Systematic quality control**

Roto provides premium quality hardware technology and provides evidence of it in systematic, certified testing processes that employ state-of-the-art measuring methods. The Roto NT special surface undergoes wide-ranging tests that go well beyond the current standards and regulations. Climate tests conducted in accordance with the most stringent testing requirements ensure that each individual component of the NT modular system meets the strictest quality requirements.

### **10 years warranty on Roto NT**

All NT components undergo such stringent quality control that they are proven to be able to withstand at least 10 years in daily use. This is the only way to achieve extraordinary quality. On the basis of the special coating technology and the high testing and quality standards, Roto offers its well-known 10-year warranty on the functional capability of all NT components used in Tilt&Turn products and Tilt&Slide Patio elements. High-value products of reliably high quality – what the Roto brand stands for.



**Roto Frank AG**  
**Window and door technology**

Wilhelm-Frank-Platz 1  
70771 Leinfelden-Echterdingen  
Germany  
Telephone +49 711 7598-0  
Telefax +49 711 7598-253  
info@roto-frank.com  
www.roto-frank.com



**Roto International**

All locations and sales partner details at:  
[www.roto-frank.com](http://www.roto-frank.com)

Argentina	China	Great Britain	Netherlands	Slovenia
Austria	Croatia	Greece	Poland	Spain
Belarus	Czech Republic	Hungary	Portugal	Switzerland
Belgium	Estonia	Italy	Romania	Turkey
Bosnia- Herzegovina	France	Latvia	Russia	Ukraine
Chile	Georgia	Lithuania	Serbia	USA
	Germany	Mexico	Singapore	